

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 60-141768

(43)Date of publication of application : 26.07.1985

(51)Int.Cl.

C09D 3/66  
C09D 3/52  
// C08G 63/12  
C08G 63/76

(21)Application number : 58-249944

(71)Applicant : TOYOBO CO LTD

(22)Date of filing : 28.12.1983

(72)Inventor : NAGAI HIROSHI

NAITO IORI

TOGAWA KEIICHIRO

MIZUMURA YUTAKA

## (54) COMPOSITION FOR COATING STEEL PLATES

(57)Abstract:

PURPOSE: The titled composition that is composed of a modified polyester resin obtained from a specific polyester resin and an epoxy resin and of an alkyl- etherified formaldehyde resin, thus showing excellent adhesion to metal, good foldability, high scratch resistance and erosion resistance.

CONSTITUTION: The objective composition is obtained by mixing e.g., (A) 30W 97wt% of a modified polyester resin obtained by reaction between (i) a polyester from the carboxylic components of 55W 99mol% of aromatic dicarboxylic acid, 45W 1mol% of aliphatic or alicyclic dicarboxylic acid and at least one of polycarboxylic acid selected from aromatic tri- or more carboxylic acids and from the glycol components of 20W 80mol% of alkylene oxide adduct to bisphenol A and 80W 20mol% of 2W 6C aliphatic polyhydric alcohol and (ii) an epoxy resin, with (B) 3W 30wt% of an alkyl-etherified formaldehyde resin and, when necessary, (C) 0W 60wt% of pigments.

any of (A), (B), (C) with (ii)

## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

A → i + ii  
A + B (optional) C